

GMEET HD ROOM9200 4-site MCU

Full HD Video Conferencing System

Perfect for any budget, the GMEET HD Room9200 is GMEET affordable, 4-site, high performance MCU video conferencing system. This all-in-one video conferencing solution allows organizations to start conferencing immediately, with no installation fees or costly upgrades. Our patented, intelligent microphones can be linked together to form a daisy chain so you can enjoy great audio reception in any size of conference room. All these great features make the GMEET HD ROOM 9200 the perfect communication solution. Users can also connect to the GMEET HD ROOM 9200 from PCs, Laptops, tablets and smart phones via GMeet Software.



Full HD video & HD content sharing

Experience natural, real-time video communication on one monitor at HD 1080p 60fps, while sharing presentation les, animation, visualizer images and more on another at HD 720p 60fps, creating a smooth, interactive video conferencing experience.



PTZ Camera with 12X Zoom

The GMEET HD Room 9200's powerful full HD PTZ camera offers 12X optical zoom, as well as +/-130° pan and +90°/-25° tilt, quick auto-focus and clear close-ups of participants, making it ideal for large conference rooms.



GMEET HD Room 9200 cameras offer the following features:

- High definition video transmission
- Clear, crisp natural colors from precisely tuned optics
- Quick, fluid movements with sharp focus



Remote Controller

No need to waste time panning and zooming manually during GMEET HD Room video conferences – simply program presets on the remote control ahead of time, and during meetings you can shift the camera from a wide view of the room to a close-up of an object with just the press of a button.

GMEET HD Room9200

4-site MCU

Full HD Video Conferencing System

Package contents Video standards

- Main system unit (codec)
 - The New PTZ camera
 - Microphone array
 - IR remote control
 - Power supply
 - Cables
 - Warranty card
 - Quick guide
- H.264, H.264 HP, H.264 SVC, H.263+, H.263, H.261
 - H.239 dual video streams
 - BFCP content sharing

Video features

- 3D Denoise

Video inputs

- HDMI
- DVI (HDMI)

Video outputs

- HDMI
- DVI(HDMI)

Communications

- H.323, SIP standards, SIP TLS
- 64Kbps~4Mbps
- RJ45 network LAN (10/100/1000)
- Manual bandwidth settings

Camera

- The New PTZ:
 - pan/tilt/zoom camera
 - 2-megapixel CMOS sensor
 - 12X total zoom (12X optical zoom)
 - ±130° pan; +90°/-25° tilt
 - 72° FOV (H); 43° FOV (V); 82° FOV (D)

People video resolutions

- HD1080p (1920 x 1080)
- HD720p (1280 x 720)
- 480p (848 x 480)
- 4CIF (704 x 576)
- CIF (352 x 288)
- SIF (352 x 240)
- All resolutions at 60fps

Content video resolutions

- Supported resolutions:
 - HD1080p (1920 x 1080)
 - WSXGA+ (1680 x 1050)
 - SXGA (1280 x 1024)
 - WXGA (1280 x 768)
 - HD720p (1280 x 720)
 - XGA (1024 x 768)
 - SVGA (800 x 600)
 - D1 (720 x 480)
 - VGA (640 x 480)
- Output resolutions:
 - HD1080p (1920 x 1080) up to 60fps

Audio standards

- G.711, G.722, G.722.1, G.728, G.722.1C

Audio features

- Automatic gain control (AGC)
- Advanced noise reduction
- Acoustic echo cancellation (AEC)

Audio inputs

- Microphone daisy chain up to 4
- DVI (HDMI)
- Line-in (3.5 mm)

Audio outputs

- HDMI
- Line-out (3.5 mm)

Other supported standards

- H.224, H.225, H.245, H.281, H.323 Annex Q, H.460, SRTP

User interface

- Multiple layout styles
- User-friendly
- Display/edit site name

Network

- 10/100/1000Mbps
- NAT/firewall traversal
- High Efficiency Lost Packet Recovery (HELPeR™)
- API support via Telnet
- Wake-on-LAN (WOL) support
- IPv4 and IPv6 support
- Network Test
- QoS

Security

- AES (Advanced Encryption Standard) function (128-bit)
- Password protection for system settings
- Password protection for remote system management

Web management tool

- Remote management
- Live monitoring
- Firmware update
- Phonebook download/upload/edit
- Restore system settings
- Export call history

Value-added features

- Meeting recording
 - In meeting and offline recording
 - Save directly to USB flash drive
 - Supports screen re-layout during playback
 - Playback
- Speed dialing via hot keys (10 sets)
- Camera presets (100 positions)
- Network Time Protocol (NTP)
- License upgrade to 6, 8, 10 points
- Screen Share support
- VCLink support
- Snapshot support
- Group Calling
- Supports SIP voice calls

Power supply

- AC 100V~240V, 50/60Hz
- Consumption: EIAJ 12V, 4A

Environmental data

- Operation temperature: 0 ~40°C
- Operation humidity: 20% ~80%
- Storage temperature: -20 ~60°C
- Storage humidity: 20% ~80%

Warranty

- 3-year standard warranty*

Optional accessories



microphone



camera mount

Optional Cameras 15x/20x.

* For detailed warranty information, please contact an GMEET representative.

GMEET
HD Video Conference

CE RoHS
COMPLIANT

© 2016 Globalone Technologies Inc. All rights reserved.

All rights of this object belong to Globalone Technologies Inc. Reproduced or transmitted in any form or by any means without the prior written permission of Globalone Technologies Inc. is prohibited. All information or specifications are subject to change without prior notice. "Globalone" is a trademark owned by Globalone Technologies Inc. Other trademarks used herein for description purpose only belong to each of their

GlobalOne Technologies Inc.,
4152 Meridian St.Suite 105-435, Bellingham,
Seattle
WA 98226 United States

Presence
USA.Canada.EMEA.APAC and India
email : sales@globalone.co.in
Call : +14255776598, www.globalone.co.in

India Office
504,Sigma, Hiranandani Gardens,
Powai, Mumbai - 400076
Call : 18602676338/ +912261331212