

## GMEET ROOM SOLUTIONS VC 520 Video Conferencing Room Solutions

### GMEET VC 520, Designed for small and Medium Meeting Rooms

GMEET VC520 is a perfect conference solution that combines audio and video. It applies advanced ISP processing algorithms to provide vivid images with a strong sense of depth, high resolution, and fantastic colour rendition. The audio adopts the international advanced new-generation high-definition voice processing technology with clear and smooth sound quality and strong environmental adaptability. It can provide participants with smooth and natural audio visual effects whenever and wherever, and provide comfortable and immersive experience for teleconferencing and other applications.



#### Key Features:

- It adopts 1/2.8 inch, 2.07 megapixel high quality CMOS sensor. Resolution is up to 1920x1080.
- 5x/10x zoom lens, with 72.5 ° wide view angle without distortion.
- Leading auto focus algorithm makes lens a fast, accurate and stable auto-focusing.
- Low Noise CMOS effectively ensure high SNR of camera video. Advanced 2D/3D noise reduction technology is also used to further reduce the noise, while ensuring image sharpness.
- Adopting high accuracy step motor and motor driving controller to make extremely quiet and smooth rotation .
- Multiple Audio/Video Compression Standard.
- Support H.264/H.265 video compression.
- Support AEC(Acoustic Echo Cancellation), AGC(Automatic Gain Control), NC(Bidirectional noise compression), Automatic Direction finding Technology of Intelligent microphone(EMI).
- Built-in 4 single-point microphones, composed of 360-degree omni-directional audio-pickup, 6m sound-pickup diameter, external microphone is available, up to 10m sound-pickup diameter .
- Support Windows, Android, IOS and Linux.
- Support Bluetooth connection and hands-free conference calls on mobile phones.
- Speaker volume reaches 95dB, digital adjustment for 16 levels speaker volume.
- Built-in infrared receivers. The IR remote controller is available for every corner of the conferencing site.
- Built-in Up/Down, Left/Right, Answer, Hang up, Bluetooth, Presets, and other keys.
- Centralized connecting with the centralized controller, the wiring is simpler and more nice.
- Easy to use, install and maintain.

Technical Specification

<b>Sensor</b>	1/2.8 inch high quality HD CMOS sensor
<b>Effective Pixels</b>	2.07M, 16: 9
<b>Video Format</b>	176x144/320x240/320x180/352x288/640x480/720x480/720x576/640x360/800x600/960x540/1024x576/1024x768/1280x720/1920x1080P30/25/20/15/10/5
<b>Optical zoom lens</b>	5x/10x optical zoom, f=3.1 ~ 15.5mm
<b>View angle</b>	20°9(tele) 83.7°(wide)
<b>Aperture value</b>	F1.8 – F2.8
<b>Digital Zoom</b>	X10
<b>Minimum Illumination</b>	0.5Lux(F1.8, AGC ON)
<b>DNR</b>	2D&3D DNR
<b>White Balance</b>	Auto / Manual/ One Push/3000K/3500K/4000K/4500K/5000K/5500K/6000K/6500K/7000K
<b>Focus</b>	Auto/Manual/One Push
<b>Aperture/Electronic Shutter</b>	Auto/Manual
<b>BLC</b>	ON/OFF
<b>WDR</b>	OFF/ Dynamic level adjustment
<b>Video Adjustment</b>	Brightness, Colour, Saturation, Contrast, Sharpness, B/W mode, Gamma curve.
<b>SNR</b>	>55dB
<b>Rotation angle</b>	Pan: -125° ~ +125°, Tilt:-30° ~ +30°
<b>Control speed</b>	Pan: 0.1 ~ 65°/sec, Tilt:0.1 ~ 35°/sec
<b>Present speed</b>	Pan: 65°/sec, Tilt: 35°/sec
<b>Voice technical parameters</b>	Acoustic Echo cancellation(AEC)>65dB Echo length cancellation: ≥400ms Bidirectional noise compression(NC): <25dB Automatic Direction finding Technology of Intelligent microphone(EMI) Automatic gain control(AGC)
<b>Audio parameters</b>	Microphone frequency response: 100Hz-22KHz Speaker frequency response: 100Hz-22KHz Speaker volume: 95dB at the most Microphone sound-pickup diameter: 6 meters, 360 degrees full range
<b>Bluetooth</b>	Bluetooth devices available
<b>IR Reception</b>	Angle: 360° Distance: 10m IR Transparent transmission available
<b>External Mic (optional)</b>	2 external microphones can be connected, making the sound-pickup diameter up to 10 meters
<b>Dimensions</b>	200mm×200mm×55.9mm (L×W×H)
<b>Interface</b>	Mini DIN6 ×2 Power interface×1 Power switch×1 Mini USB interface×1
<b>Power supply</b>	Adapter input AC110V-AC220V, output DC12V/1.5A
<b>Data line</b>	Mini DIN6 data line ×2 Length: 5m(10m/15m for options)
<b>USB cable</b>	USB2.0 cable Length: 3m
<b>Compatibility</b>	Support Windows, Android, IOS and Linux
<b>Dimensions</b>	Hub 100mm×62mm×27mm (L×W×H) Speaker/MIC 200mm×200mm×55.9mm (L×W×H)
<b>Accessories</b>	Power adapter, Remote control, cables